Small Conservational Multichannel ACM Data Logger SACM-318B

Specifications

[Overview]

It is a logger that can measure from ultra-micro current to large current of ACM sensor with an auto-range non-resistance ammeter. In addition to an external power supply, the power-saving design enables long-term battery operation. Corrosion rate, wetting time, and amount of sea salt adhesion can be determined by analyzing ACM data. It is also possible to measure the temperature and humidity data for calculating the sea salt adhesion amount. Up to 8 ACM sensors and 2 temperature/humidity sensors can be connected per unit. The data is saved in the SD card, and it can be extracted and read on a PC.

[SACM-318B Structure/ Appearance]



The time, the measurement interval can be adjusted, and the measured value can be checked on an LCD display. Since the main unit is waterproof and can be used outdoor (batteries and terminals are separated). If the waterproofness wants to be strengthened, please use the separately sold waterproof box.

If you have an external power source, use the AC adaptor. It can be powered by a 12V battery in the absence of an external power source, and when coupled with a photovoltaic power generating system, it is feasible to monitor for extended periods of time.

[Specifications]

Number of Measurement	ACM Sensor: max. 8
Channels	Temperature-Humidity Sensor: max. 2
ACM Sensor Measurement	Range: 10nA、 100nA、 1uA、 10uA、 100uA、 1mA、 10mA
	Auto Switching(With Noise Reduction Filter)
LCD Display	2 lines, 16 columns (no backlight)
Data Acquisition and	10 mins interval (Adjustment Possible), Text Format(readable by
Format	spreadsheet software, etc.)
Data Storage	SD Card (Up to 2GB)
Power Supply, Logger's	DC9~12V Approximately 1kg
weight	DC9 -12v Approximately 1kg
External Dimensions	$280\text{mm}(W) \times 190\text{mm}(D) \times 141\text{mm}(H)$ (Excluding Protrusion and Cable)

SACM-318B (Main body)

Power Supply Cable

AC Adaptor







Industrial SD Card

ACM Sensor

Temperature-Humidity
Sensor







OAccessories

Power Supply Cable

OSeparated Purchase Required

AC Adaptor SD Card

XIt is recommended to purchase the specified product for compatibility with the equipment.

OType of Sensor

ACM Sensor, Temperature-Humidity Sensor

